

## CPSS

## CPSS SINGLE-PHASE TECHNICAL DATA SHEET

MODEL		CPSS 4000	CPSS 6000	CPSS 8000	CPSS 10000	
POWER	VA	4000	6000	8000	10000	
	W	3500	5250	7000	8500	
INPUT	Rated voltage*	110 – 280 Vac				
	Frequency	45 – 70 Hz				
	Power factor	>0.99				
	Current distortion (THDi)	<5%				
OUTPUT	Rated voltage	200/208/220/230/240 Vac selectable				
	Voltage distortion	<2% with linear load, <7% with distorting load				
	Voltage stability	±1%				
	Frequency	50/60 Hz (selectable)				
	Frequency regulation	±1Hz, ±3Hz selectable				
	Frequency stability	≤ 0.2% (free running)				
	Power factor	0.875			0.85	
	Crest factor	3:1				
	Waveform	Pure sine wave				
	Output connection	Screw terminal block				
	Capacity @ 100 % load	4000 VA/3500 W	6000 VA/5250 W	8000 VA/7000 W	10000 VA/8500 W	
	Overload @ 120% permanent load	4200 VA/4200 W	6300 VA/6300 W	8400 VA/8400 W	10200 VA/10200 W	
	EFFICIENCY	VFI mode	Up to 93%			
		ECO mode	Up to 97%			
In battery		Up to 94%				
GENERAL	Dimensions (WxDxH) mm	288x700x513				
	Weight (kg)	41		42		
	Alarms	Audible and visual alarm alerts for: incorrect battery polarity, short circuit, power failure, low battery, bypass transfer, and UPS fault, etc.				
	Protection	Battery polarity, short circuit, overload, overheating, deep discharge, overcharging.				
	Operating mode	Multimode: VFI, ECO, Emergency (SE), Mixed mode (SA and SE with separate outputs)				
	Cold start from the battery without mains power	Included				
	Protection class	IP20				
	BATTERY - CHARGER	Battery type	12V VRLA, AGM (maintenance-free lead)			
Number of batteries		20 units (120 cells)				
Charging time		80% of the battery capacity within 12h				
Internal battery charger		4 A Standard (additional 4 A with optional kit)				
External battery cabinet connections		Plug-in & Play				
ENVIRONMENTAL PARAMETERS	Operating temperature**	0 – 40°C				
	Relative humidity	0% – 90% (without condensing)				
	Altitude (a.s.l.)	<1000 m with no power derating, >1000 m with 1% derating for every 100 m				
	Audible noise at 1 m	≤60 dBA				
CONNECTIVITY	Built-in communication ports	USB, RS232, EPO On/Off contact, and additional slots for optional cards				
	User interface	LCD and function keys (parameters: voltage, frequency, load percentage, battery voltage, output voltage, estimated uptime, UPS temperature).				
	Optional accessories	Cards: SNMP, RS485 ModBus, dry relay contacts				
	Compatible software platforms	Microsoft Windows, Linux, Mac OS, VMware				
REGULATIONS	Standards	EN 50171, IEC EN 62040-1, IEC EN 62040-2, IEC EN 62040-3				
	Marking	CE, UKCA				

\* Subject to conditions \*\* To be verified according to the battery parameters

# CPSS

## CPSS THREE-PHASE TECHNICAL DATA SHEET

MODEL		CPSS 3P 10 KVA	CPSS 3P 20 KVA	CPSS 3P 30 KVA	CPSS 3P 40 KVA
POWER	kVA	10	20	30	40
	kW	9	17	27	33
INPUT	Rated voltage	400 V three-phase with neutral			
	Voltage tolerance	±20%			
	Rated frequency	40 – 70 Hz			
	Power factor	≥0.99			
	Current distortion (THDi)	≤ 4% at full load	≤ 3% at full load		
OUTPUT	Rated voltage	380/400/415 V three-phase+neutral			
	Voltage stability	±1% (static load)			
	Frequency	50/60 Hz			
	Frequency stability	±0.01% (free running)			
	Power factor	0.9	0.85	0.9	0.825
	Crest factor	3:1			
	Voltage distortion	≤2% with linear load, ≤5% with distorting load			
	Permissible overload	120% permanent load, 125% for 10 minutes, 150% for 1 minute			
EFFICIENCY	VFI mode	Up to 95%			
	ECO mode	Up to 98%			
	In battery	Up to 94%			
GENERAL	Parallel connection	Up to 6 units			
	Dimensions (WxDxH) mm	260x850x890 (including wheels)			
	Weight (kg)	74	76	85	88
	Alarms	Audible and visual alarm alerts for: incorrect battery polarity, short circuit, power failure, low battery, bypass transfer, and UPS fault, etc.			
	Protection	Battery polarity, short circuit, overload, overheating, deep discharge, overcharging.			
	Operating mode	Multimode: VFI, ECO, Emergency (SE), Mixed mode (SA and SE with separate outputs)			
	Cold start from the battery without mains power	Included			
	Protection class	IP 20			
	BATTERY	Number per string (12V)	40 pcs		
Common battery for parallel configuration		Supported			
Internal battery (optional)		Up to blocks 40 12 V 7/9 Ah batteries		N.A.	
Max. charging current*		12.9 A	14.5 A	24.7 A	28 A
Cold start from the battery without mains power		Included			
BYPASS	Rated voltage	380/400/415 V three-phase+neutral			
	Voltage tolerance	Basic window ±10% (programmable ±5% – ±15%)			
		Critical window ±25% (programmable ±16% – ±30%)			
	Frequency	50/60 Hz			
	Frequency tolerance	±1 Hz / ±3 Hz (selectable)			
Protection	Fuses				
ENVIRONMENTAL PARAMETERS	Operating temperature**	0 – 40°C			
	Altitude (a.s.l.)	<1000 m with no power derating, >1000 m with 1% derating for every 100 m.			
	Relative humidity	0 – 95% (without condensing)			
	Audible noise at 1 m.	<52dB		<55dB	
CONNECTIVITY	User interface	4.3" colour LCD touch screen display with removable SD card			
	Built-in communication ports	USB, RS232, EPO, 3 out dry relay contacts (programmable) and two additional slots for optional cards			
	Optional accessories	Cards: SNMP, RS485, ModBus, 6 in/6 out dry relay contacts, touch panel for remote monitoring, Mixed mode kit			
REGULATIONS	Standards	EN50171, IEC EN 62040-1, IEC EN 62040-2, IEC EN62040-3			
	Marking	CE, UKCA			

\* Subject to conditions \*\* To be verified according to the battery parameters